



Foreman/Supervisor's Signature: \_

## Tailgate/Toolbox Safety Training Safety Services Company-Safety Meeting Division, PO Box 6408 Yuma, AZ 85366-6408 Toll Free (866) 204-4786



Compan	y Name:	Job Site Location:	(T) (T)
Date:	Start Time:	Finish Time: Foreman/Supervisor:	
		Topic 222: OSHA's Top Ten	
Governm approved employer Even wit Statistics During a	ent has determined that every worker OSHA which, at a minimum, must is to provide a safe, healthful workplant all the regulation, each year there are published by the Department of Lab typical workday in the United State	ealth Administration (OSHA) is the government entity that monitors and regulates we in the United States is entitled, without exception, to a safe workplace. Some 23 States conform and comply with Federal OSHA standards. The mission of these agencies and the employee training to recognize and resolve unsafe conditions and practice hundreds of thousands of injuries and thousands of fatalities.  For report that there are presently around 93 million workers in more than 6 million works, more than 17 thousand are hurt at work, there are more than a dozen on-the-job	States have their own cies is to compel all ees in the workplace. rkplaces in America. fatalities, and many
dozens die from work related illnesses. Aside from all of this human suffering, workplace injuries cost the U. S. economy billions each year.			
Following are the 10 most frequently cited OSHA violations for construction contractors:			
0		of Scaffolding (6300 citations) Regulations require that "scaffolds shall a shall be constructed and loaded in accordance with that design."	
2	Fall Protection: Scope/Applications/Definitions (3522 citations) Regulations require that "employers must provide appropriate fall protection systems when an employee may fall more than 6 feet to a lower level."  Conventional systems include personal fall arrest systems, guardrail systems, and safety net systems.		
3	Ladders (1204 citations) Regulations require that "ladders be inspected by a competent person for visible defects on a periodic basis and after any occurrence that could affect their safe use. Portable ladders with structural defects, such as, but not limited to, broken or missing rungs, cleats, or steps, broken or split rails, corroded components, or other faulty or defective components, shall either be immediately marked in a manner that I. D.'s them as defective, or be tagged with "Do Not Use" or similar language, and shall be withdrawn from service until repaired."		
4	Head Protection (1106 citations) Regulations require that "employees working in areas where there is a possible danger of head injury from impact or from falling or flying objects, or from electrical shock and burns, shall be protected by protective helmets."		
(\$)	Hazard Communication (986 citations) Regulations require that "employers must provide employees with training and information on hazardous chemicals in their work areas at the time of initial assignment or whenever a new hazard is introduced."		
6	Electrical: Wiring Design and Protection (921 citations) Regulations require that "employer shall use either ground fault circuit interrupter equipment or an assured equipment grounding conductor program as specified"		
Ø	daily inspections of excavations, adja-	s (916 citations) Regulations require that "a competent person shall make cent areas, and protective systems for evidence of a situation that could result lure of protective systems, hazardous atmospheres, or other hazardous conditions."	
8	Electrical Wiring Methods, Components and Equipment, General Use (912 citations) Regulations require that "for temporary wiring over 600v, nominal, fencing barriers or their effective means shall be provided to prevent access of other than authorized or qualified personnel. Electrical feed shall originate in a distribution center, branch circuits shall originate in a panelboard or power outlet. Receptacles shall be of the grounded type and flexible cords shall be protected."		
9		ons) Regulations require that "employers shall provide a training program for each	
(1)	Manually Propelled Mobil Ladder Stands and Scaffolds (837 citations). Regulations require that "lift controls shall be tested each day prior to use to determine that such controls are in safe working condition. Only authorized persons shall operate an aerial lift. A body belt shall be worn with a lanyard attached to the boom or basket when working from an aerial lift."		
and illnes workplace and how	on: Compliance with OSHA Standardsses. In fact, OSHA standards provide, it is the employer's responsibility to recognize and avoid hazards. It is	ds is the law; however, compliance with these standards alone will not prevent all injust minimum acceptable levels of protection. In order to prevent injuries and illnesses in provide the necessary training so that employees know what the safety requirements hen also the employee's responsibility to learn the safety requirements and put this trackeep this information in mind and do your part to keep your workplace safe.  **Work Site Review**	ries n the are
Work-S. Personn	ite Hazards and Safety Suggestion el Safety Violations:	s:	
Employee Signatures:		(My signature attests and verifies my understanding of and agreement to comply with, all co and regulations, and that I have not suffered, experienced, or sustained any recent job-re	lated injury or illness.)